

## CAT6 PATCH PANEL

InBERG Category6 unshielded patch panel complies with TIA/EIA-568-C. The construction in standard size, suits all 19" rack installation.

### Application :

- 10GBASE-T
- 1000BASE-T
- 100BASE-T4
- 100BASE-TX
- 100BASE-T



### Specification for Cat6 UTP Patch Panel :

Electrical	Voltage Rating : 125 VAC RMS
	Current Rating : 1.5AMP
	Contact Resistance : 100 Millions MAX.
	Insulation Resistance : 1000 MEGOHMS MIN @ 500 VDC
	Dielectric Strength : 750 VAC RMS 60Hz ,1 MIN
Environmental	Storage : -40~ 85°c
	Operation : 0~70°c
Mechanical	Housing Material: PBT+30%GF UL94V-0
	Panel Frame : Carbon Steel, Powder Coating in black color
	Contact Material : PC UL94V-0
	Contact : Phosphor Bronze with Nickel Plating

### Ordering Information for Cat6 UTP Patch Panel :

Part Number	Description
IB-CAT6-24PL-JK	CAT6 1U 24PORT PATCH PANEL, LOADED
IB-CAT6-48PL-JK	CAT6 2U 48PORT PATCH PANEL, LOADED