

Cat6A UTP Keystone Jack

InBERG Cat6A Keystone Jack

InBERG Cat.6A UTP Keystone Jack offers exceptional performance that will support 5GBASE-T Ethernet with complete reliability. Our Keystone Jacks are suitable to be assembled with the InBERG unloaded Patch Panels and faceplates for the wall outlet.

Our Cat.6A keystone jacks are designed to support any data or voice protocol that is capable of running over a Cat.6A cabling system and backward compatible with the existing network infrastructure.



Specification for Cat6A Keystone jack:

Standard	ISO/IEC 11801 & TIA/EIA 568.2-D
Electrical	Voltage Rating : 125 VAC
	Current Rating : 1.5AMP
	Contact Resistance : 100 MILLIOHMS MAX
	Insulation Resistance : 1000 MEGOHMS MIN@500VDC
	Dielectric Strength : 750 VAC RMS 60Hz ,1 MIN
Environmental	Storage : -40~ 85°c
	Operation : -40~85°c
Mechanical	Housing Material: UL94V-0
	Insert Material: UL94V-0
	PCB Material : FR-4
	Contact Material : Phosphor Bronze
	IDC Contact Material : Phosphor Bronze
	Wire : AWG 22~24
	Conform to ANSI/TIA/EIA-568.2-D

Ordering Information for Cat6 Keystone Jack:

Part Number	Description
IB-CAT6A-JK	CAT6A UTP Keystone Jack