



PDU Technology Specification

Date: 07/04/2019

NO.: HKIB0341907010


Customer		RoHS	
		Yes	
Product Name		Customer's Code	
Designated Power Distribution Unit for Cabinet			
Part Number		Picture Code	
IBPDU2220H1-16AVFNMB-B2		HKIB0341907010	
No.	Item	Detailed Description	
1	Product Series	IBPDU2220	
2	Socket Type	BS1363 45degree[8];Single IEC320 C13 Socket(Right)[8];	
3	Socket Quantity	16	
4	Power Input	Left end single input (Bottom input)	
5	Bracket Install	Inverse installation	
6	Cable with plug	IEC60309 plug (32A 2P+E)	
7	Control Function	No controlling function	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 6.0 mm ² x 6M	
11	Product Size	L x W x H = 981.8 x 44.4 x 62 mm	
12	Mounting Length	622.3 mm (Tool-less installation)	
13	Case Length	925.8 mm	
14	PDU Exponent	1.689	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut, PDU manual	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	IBPDU2220H1-16AVFNMB-B2
		Rating voltage	250VAC 50/60Hz
		Rating Current	32A
		Max. Current	
		Max. Power	8000W
		Safety Authentication	CE
		Logo	RoHS
		Producer	
No.	Add-In		
1	Socket assemble	NO	
2	Interior Connection Wire	4.0 mm ² (12AWG)	
3	Interior Connection Style	Group connection	
4	Fix the Cable	Cable clamp(19)	
5	Module Assemble (from left to right)	Please refer to the drawing	
6	Others	NO	
Made by: Jessica		Customer confirm:	
		Check:	
		Authorize:	

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

Preview



IEC60309 plug (32A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)				
Length: 981.8	Mounting length: 955.8		Customer	
Width: 44.4	Case length: 925.8		Product name	Designated Power Distribution Unit for Cabinet
Height: 62	case tolerance: ± 1.0		Part number	IBPDU2220H1-16AVFNMB-B2
	SIGN	DATE	Customer's code	
DRAWN	Jessica	07/04/2019	Drawing number	HKIB0341907010
CHK'D			Edition number	
APP'D				